

**SPECIFICATION**

Attorney Docket No. 13154.005

**TO ALL WHOM IT MAY CONCERN:**

BE IT KNOWN that I, Ken Barnard, have invented new and useful improvements in a

**GARAGE DOOR WINDOW FRAME AND METHOD OF INSTALLATION**

of which the following is a specification:

<i>"EXPRESS MAIL" NO. EL929456374 US</i>	
I hereby certify that this paper or fee is being deposited with the United States Postal Service as "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated below and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.	
Date of Deposit: <u>8-18-03</u>	By: <u>Sarah Harner</u>

## BACKGROUND OF THE INVENTION

### A. Field of the Invention:

This present invention relates to decorative molding assemblies for framing openings of residential or commercial structures, and more specifically to a decorative window frame assembly for decoratively framing a garage door window opening of a residential or commercial garage door.

### B. Description of the Prior Art

Modern garage door systems are typically comprised of doors having horizontally arrayed sections joined by hinges into a door unit. The door is mounted in a vertical track which curves upwardly into a horizontal position so that the door may be opened upwardly and supported horizontally in an open position. The sections are joined by the hinges along the longitudinal edges of the sections so that the overall door structure will generally conform to the radius of curvature of the track as it changes from vertical to horizontal. Customarily, each of the sections are fabricated separately and thereafter hinged together along a longitudinal edge to provide the complete overhead door structure.

Historically, the sections are fabricated from a galvanized and/or prepainted sheet metal stock which has been rolled or otherwise formed into the particular section facing, web and parallel interior flange configurations. Vertical stiles are usually secured to the section facing and interior flanges at spaced locations by spotweld or rivet techniques. Most prior art overhead door systems use hinges that are secured directly to the section stiles. While a majority of garage doors continue to be manufactured from mild steel stock, some manufacturers offer overhead doors made from synthetic materials such as various types of vinyl.

Molding assemblies are used in a variety of applications to frame or "surround" doorways, windows, patio doors, garage doors etc., to provide a decorative, aesthetically appealing framing for the opening. In recent years, these surround molding assemblies have been manufactured from plastics

1 and are often injection molded. In general, plastics provide significant advantages in most  
2 installations. For example, molding or framing assemblies or components thereof manufactured from  
3 plastic are low in maintenance. Plastic molding assemblies are not susceptible to moisture and  
4 therefore will not typically decay, warp or splinter. Advantageously, plastic surround molding  
5 assemblies or components thereof can be sawed, drilled, glued or nailed. Still further, during the  
6 manufacture of plastic molding assemblies, plastic can be tinted with dyes or other materials to  
7 provide molding assembly components which are of desired colors, thus obviating the need for  
8 painting prior or subsequent to installation on a structure. Molding plastics are also available as UV  
9 stable materials which are resistant to degradation upon exposure to the surrounding environment.

10  
11 Particularly in the area of residential garage doors, a number of manufacturers offer plastic window  
12 frame assemblies which are fitted within openings provided in the garage door and which typically  
13 feature a central opening which contains a transparent pane which may be of glass, plastic or such  
14 newer materials as acrylics. The central opening in the window frame assembly may also contain a  
15 decorative trim member which is sandwiched between the transparent pane and other framing  
16 components .

17  
18 The prior art window frame assemblies for overhead garage doors have typically been assembled in  
19 a "stick built" fashion using mounting clips. A front frame member of injection molded plastic is  
20 received into the door opening from the front side. The front frame member has a central opening  
21 for receiving the window pane, decorative trim, etc. The front frame member and pane and then  
22 retained in position by hammering four mounting clips, sometimes referred to as "stick" strips, on the  
23 back side of the door. The front frame member has an inner periphery equipped with a locking rail  
24 which matingly engages a groove in the locking strips. The locking strips have corners which are  
25 diagonally cut and fit. Once hammered into position, it was generally necessary to cut off the locking  
26 strips in order to disassemble the window frame components in order to, for example, replace the  
27 pane. Thus, while the prior art technique was generally effective in securing the window frame  
28 assembly to the door structure, the use of stick built framing techniques added to the time and  
29 expense associated with installing the complete assembly. Once installed, should one component of

1 the surround molding assembly need to be removed or replaced, the use of such an assembly  
2 technique complicated the task of removing and replacing the sub-components of the window frame  
3 assembly.  
4

5 Accordingly, it is an object of the present invention to provide a window frame assembly for an  
6 overhead garage door which provides a decorative and aesthetically pleasing appearance, while  
7 securely supporting the various window frame components.  
8

9 It is a further object to provide a versatile window frame assembly that can accommodate various  
10 other trim components that may abut the frame components.  
11

12 It is yet another object of the present invention to provide a window frame assembly for a garage  
13 door which provides a decorative, aesthetically pleasing appearance, and in which the components  
14 of the window frame assembly include reversibly interlocking portions adapted to interconnect  
15 components of the assembly together. In this manner, the decorative window frame assembly can be  
16 securely, yet releasably held to the structure, while reducing the time required for assembly and  
17 without requiring the use of nails, threaded fasteners or other like fastening elements.  
18

19 Accordingly, it is another object of the present invention to provide such a window frame assembly  
20 which can be secured to the structure in a secure fashion and yet which can be released and removed  
21 with the use of a simple hand tool such as a screw driver.  
22  
23

## SUMMARY OF THE INVENTION

In view of the foregoing, it would be an advancement in the art to provide a garage door window system having a molded plastic frame which is assembled in snap-fit fashion, which can be quickly and easily disassembled, and that is characterized by the absence of mounting clips to accommodate easy replacement of the window. Such a novel garage door window system is disclosed and claimed herein.

The window frame assembly of the invention is used to install a transparent pane or a decoration trim within an opening provided in a metal, overhead garage door having front and rear exposed surfaces and at least one window opening therein. A front window frame member is formed in one piece of a synthetic, polymeric material and has a periphery sized to circumscribe the window opening from the front exposed surface of the door. A rear window frame member, also formed in one piece of a synthetic polymeric material, has a periphery sized to circumscribe the window opening from the rear exposed surface of the door. The front and rear window frame members have engagement elements located about the peripheries thereof which snap together in mating fashion to thereby mount the frame members within the window opening. The engagement elements are also disengageable with a hand tool to separate the frame members and remove the members from the window opening.

Preferably, the front and rear window frame members are injection molded from a suitable plastic and the engagement elements are tabs provided on one respective frame member for engaging aligned lips provided on the other respective frame member. For example, the tabs can be provided on a rear surface of the front window frame member and the lips can be provided on a front surface of the rear frame member. In the most preferred form of the invention, the rear frame member has openings provided therein in alignment with the engagement tabs, the openings providing access to the engagement tabs so that a hand tool can be inserted within the openings to disengage the tabs from the lips to allow the disassembly of the window frame members from within the opening in the garage door.

1 In the method of the invention, a window assembly is installed within a metal garage door having  
2 front and rear exposed surfaces and at least one opening provided therein. A front window frame  
3 member is formed in one piece of a synthetic, polymeric material, the front window frame member  
4 has a central opening and has a periphery sized to circumscribe the window opening from the front  
5 exposed surface of the door. A rear window frame member is also formed in one piece of a synthetic  
6 polymeric material and has a central opening and a periphery sized to circumscribe the window  
7 opening from the rear exposed surface of the door. Snap-fit engagement elements are provided about  
8 the peripheries of the front and rear window frame members which snap together in mating fashion.  
9 The front window frame member is installed within the garage door opening on the front exposed  
10 surface thereof. A transparent pane is installed within the central opening of the front window frame  
11 member. The rear window frame member is then installed on the opposite, rear exposed surface of  
12 the door opening to thereby mount the frame members within the window opening with the  
13 transparent frame being sandwiched between. The inner and outer window frame members can then  
14 be pressed together in order to engage the snap-fit engagement elements. The snap-fit engagement  
15 elements are also disengageable with a hand tool to separate the frame members and remove the  
16 members from the window opening. Since the rear frame member can be easily removed, the  
17 transparent pane can easily be repaired or replaced.

18  
19 Additional objects, features and advantages will be apparent in the written description which follows.  
20

**BRIEF DESCRIPTION OF THE DRAWINGS:**

FIG. 1 is partial perspective view of a garage door having window frame assemblies of the invention installed therein.

FIG. 2 is an exploded view of a window frame assembly of the invention showing the front and back frame members with a transparent pane located therebetween.

FIG. 3 is a view of portions of the front and back frame members before being snapped together.

FIG. 4 is a view similar to FIG. 3, but showing the two halves of the window frame assembly snapped together.

FIG. 5 is front, plan view of the window frame assembly of the invention.

FIG. 6 is a side, partial cross-sectional view of the front and back frame members snapped together, also showing a portion of the transparent pane and a portion of the metal door.

FIG. 7 is a view of a corner of the frame assembly from the front with the rear frame member peripheral edge being visible.

FIG.'s 8A and 8B are partial cross-sectional views of the front and back frame members showing a screw driver in phantom lines being used to disengage the mating engagement elements.

FIG. 9 is a partial perspective view of a section of the front frame member of the invention showing a field goal shaped engagement opening.

FIG. 10 is a view similar to Fig. 9 but of the back frame member showing the corresponding tab which engages the field goal shaped engagement opening of the front frame member.

1 FIG. 11 is a partial perspective view of a portion of the back frame member showing the flexible hinge  
2 elements which are present at spaced circumferential locations about the periphery of the frame  
3 member.

4  
5 FIG. 12 is a partial, perspective view of the back side of the assembled frame showing the openings  
6 used to access the engagement elements in order to disengage the frame members and remove the  
7 back frame member.

8  
9 FIG. 13 is an exploded view of a prior art frame assembly.

10  
11 FIG. 14 is a partial, perspective view of the prior art frame assembly of FIG. 10 with the frame  
12 components being shown before being assembled together.

13  
14 FIG. 15 is a view similar to FIG. 11, but with the frame components being locked together.



## DETAILED DESCRIPTION OF THE INVENTION

As discussed briefly above, commercially available garage doors used at the present time are typically assembled from a series of door sections aligned horizontally in an edge-to-edge configuration to form a vertically oriented door for the garage opening. The sections are hinged together as a series along their abutting, horizontal edges to allow the garage door to be raised upwardly in a track to an overhead, horizontal position. The track includes a curved section between the vertical and the overhead positions. The hinged sections allow the garage door to traverse this curved section during the transition of the garage door from the vertical to the overhead, horizontal position.

In many of the presently available garage door systems, a series of decorative windows are incorporated the garage door, typically within an upper section of the garage door. These windows are formed in individual panels of the upper section and provide daylight illumination of the closed garage as well as a decorative appearance. A window opening is formed in each panel. Applicant's FIG. 1 shows a typical garage door 13 having window assemblies 15 installed into openings provided in a top section thereof. The garage door illustrated in FIG. 1 is shown in a simplified, stylized form for ease of illustration. Those skilled in the art will understand that such doors are typically provided, for example with a decorative surface treatment which is designed to mimic conventional wood panels while structurally imparting a certain degree of dimensional stability to garage door section.

Conventionally, a rather cumbersome window and window framework system is inserted in the opening provided in the garage door. A typical prior art window assembly is illustrated in FIG.'s 13-15 of Applicant's drawings. The window assembly, illustrated generally as 11 in FIG. 13, is shown in exploded fashion. In this illustration of prior art window 11, an exterior frame 16 is inserted into opening 14 followed by a windowpane 17 of glass or plastic. In many cases, a decorative overlay or "trim" (not shown) is mounted in the exterior frame 16. The exterior frame 16 is then mounted to garage door section 13 while the decorative overlay and windowpane 17 are retained in the exterior frame 16 by a plurality of mounting strips or clips 19, 23, 21, 25. The mounting clips 19, 21, 23, 25 are conventional devices and are configured with a generally U-shaped cross section having a series

1 of internally located, longitudinal ridges ( generally at 27 in FIG.'s 14 and 15) that are designed to  
2 engage corresponding longitudinal ridges 29 on the peripheral lip of exterior frame 16. Clips 19, 21,  
3 23, 25 are designed such that the edges of the U-shaped cross section are resiliently urged together  
4 thereby enabling the mounting clips to securely engage the longitudinal ridges 29 of the peripheral  
5 lip of exterior frame 16. This feature requires that a hammer must be used to force the mounting clips  
6 into engagement with exterior frame 16. Once engaged, the mounting clips are very difficult to  
7 remove in the event any component of prior art window frame assembly 11 requires replacement and,  
8 even if removed, experience has shown that the mounting clips 19, 21, 23, 25 are usually irreparably  
9 damaged during the removal process.

10  
11 The number of components that constitute prior art window frame assembly 11 and their function  
12 result in a design that is difficult to assemble as well as to disassemble. Also, the increased costs  
13 involved with the various components along with the labor required for its assembly limit its universal  
14 application for all garage door installations. For example, it was sometimes necessary in the prior art  
15 assembly techniques to mount the window frame assembly 11 into a section of the garage door before  
16 the section was assembled into the completed garage door. The garage door section would be placed  
17 onto a padded surface and the various components of prior art window 11 would be mounted  
18 thereon. The final step of the mounting procedure required that the mounting clips be vigorously  
19 pounded into place using a heavy mallet, necessitating the use of a padded surface during the  
20 mounting procedure. An additional disadvantage of the prior art window frame design and assembly  
21 technique is that the mounting clips 19, 21, 23, 25, when viewed from the garage interior, not only  
22 sag and twist but are notoriously difficult to fit with a precision, ninety-degree fit at the abutting  
23 corners of clips, especially when the mounting clips must be vigorously hammered into place.

24  
25 The combination garage door and window frame invention will now be described with respect to  
26 Figures 1-12. Figure 1 shows a typical residential garage door which includes the metal overhead  
27 garage door 13 having front and rear exposed surfaces 31, 33 (Figure 6) and at least one window  
28 opening (shown in phantom lines as 35 in Figure 2) therein.

1 A front window frame 37 is preferably formed in one piece of synthetic, polymeric material and has  
2 a periphery 39 which is sized to circumscribe the window opening 35 from the front exposed surface  
3 31 of the door 13. In the most preferred embodiment, the front window frame 37 is injection molded  
4 from a synthetic plastic such as a commercially available polyurethane or suitable polyolefin material.

5  
6 A rear window frame member 41 is also formed in one piece of injection molded plastic and has a  
7 periphery 43 which is sized to circumscribe the window opening 35 from the rear exposed surface  
8 33 of the door 13. The front and rear window frame members have engagement elements located at  
9 selected spaced locations about the peripheries 39, 43 thereof which snap together in mating fashion  
10 to allow the frame members to be mounted within the window opening 35. As will be explained, the  
11 engagement elements are also preferably disengageable with a hand tool, such as a screwdriver, to  
12 separate the frame members and remove the members from the window opening 35. Figure 3 shows  
13 the front and back frame members 37, 41 prior to being snapped together and showing a transparent  
14 pane 45 retained therebetween. Figure 4 is a similar view showing the front and back members  
15 snapped together. In a particularly preferred form of the invention, the engagement elements are tabs  
16 47 molded in the plastic of the frame member which mate with aligned lips 49 provided on the other  
17 respective frame member. As shown in Figure 3, the lips 49 may form a part of an engagement  
18 opening in the respective frame member. Figure 6 is a cross-sectional view of the assembled window  
19 taken along lines VI-VI in Figure 5 and showing the tab 47 engaging the mating lip 49 and showing  
20 the window frame assembly engaging the transparent pane 45 and being received within the opening  
21 35 provided within the metal garage door.

22  
23 The rear window frame member 41 has access openings 51 (Figure 6) provided therein in alignment  
24 with the engagement tabs 47 when the frame members are assembled. The openings 51 provide  
25 access to the engagement tabs 47 so that a hand tool can be inserted within the openings 51 to  
26 disengage the tabs 47 from the lips 49 to allow the disassembly of the window frame members 37,  
27 41 from within the opening 35 in the garage door. Figure 12 is a view from the garage interior of a  
28 portion of the isolated frame assembly showing the access openings 51 which allow access to the  
29 locking tabs 47 in order to release the tabs from the mating lips 49.

1 Figures 8A and 8B show the disassembly in which the blade of a screwdriver (indicated in phantom  
2 lines 53 in Figures 8A and 8B) is used to engage the tabs 47 from the within the rear access opening  
3 51. The resilient nature of the injection molded plastic allows the tabs to be released as shown in  
4 Figure 8B so that the frame members can be disassembled.

5  
6 In the preferred form of the invention, the tabs 47 and lips 49 are arranged in an alternating pattern  
7 at spaced locations about the periphery of the respective window frame members. The alternating  
8 nature of the tabs and lips (see tabs 48,50) are illustrated in Figure 2. While Figure 2 shows only a  
9 single transparent pane installed within the window frame assembly, it will be understood that a  
10 decorative trim insert could be installed, for example, in front of the pane 45 within the frame  
11 assembly. Such decorative trim assemblies are commercially available and known in the prior art.  
12 For example, such "Design Trim" is commercially available from National Door Industries, Inc. of  
13 Fort Worth, Texas.

14  
15 The invention has been described with respect to locking tabs 47 and lips 49 as shown in Figures 3-  
16 8B. However, Figures 9-11 illustrate a particularly preferred form of the engagement elements of the  
17 invention. As shown in Figure 9, the engagement opening and associated lip can take the form of a  
18 "field goal-shaped" opening 52 provided in the front frame member 37. The field goal-shaped  
19 opening 52 has reinforced top and bottom cross bar regions 54, 56 and reinforced side post regions  
20 58,60. With reference to the plane of the periphery 62 of the front frame member 37, the cross bar  
21 regions 54, 56 and side post regions 58, 60 form outwardly extending protrusion which strengthen  
22 the wall regions of the frame member 37 at these points.

23  
24 By providing the field goal-shaped openings with the reinforced cross bar and side post regions, the  
25 window frame members of the invention can withstand a 60 psf external and internal wind test. These  
26 features of Applicant's design provide a wind load capable/reversible snap fit for the front and back  
27 frame member.

1 Figures 10 and 11 show an additional feature of Applicant's invention which is the flexible hinges 64  
2 which are located at spaced circumferential locations about the periphery of the back frame member  
3 41. The flexible hinges 64 are planar, inwardly extending elements arranged generally parallel to the  
4 plane of the transparent pane (45 in Figure 1) which includes trench lines 66, 68. The trench lines 66,  
5 68 allow the hinge to flex to allow insertion of glazing materials, such as transparent pane 45, from  
6 the front side of the garage door with the frame in place. The flexible hinges also allow a pane of  
7 glazing to be removed more easily from the assembled frame.

8  
9 In the method of installing a window assembly of the invention, the front frame member (37 in Figure  
10 2) is first installed within the garage door opening 35 on the front exposed surface 31. A transparent  
11 pane 45 and, optionally, a decorative trim insert may also be installed either in front of or behind the  
12 pane 45. The rear window frame member 41 is then installed from the opposite, rear exposed surface  
13 33 of the door opening by simply snapping the front and rear frame members together in snap-fit  
14 fashion in order to thereby mount the frame members within the window opening with the transparent  
15 pane being sandwiched therebetween. Alternatively, the flexible hinges 64 allow a pane of glazing  
16 to be installed from the front side of the garage door even with the complete frame in place.

17  
18 If it becomes necessary to disassemble the window frame assembly, for example, to repair or replace  
19 the transparent pane, the frame members 37, 41 can easily be separated by inserting the blade of the  
20 screwdriver through the openings 51 in order to disengage the tabs 47 from the lips 49. The frame  
21 members then easily snap apart and can be removed from the door opening.

22  
23 An invention has been provided with several advantages. The garage door window frame assembly  
24 of the invention is simple in design and economical to manufacture using frame members from  
25 injected molded plastic. The front and rear frame members are provided with mating engagement  
26 means which allow the frame members to be engaged in snap-fit fashion by simply pressing the front  
27 and rear frame members together. It is not necessary to utilize a hammer or to assemble the frame  
28 members into a door section in a separate step as was often done in the prior art. The nature of inter-  
29 engageable tabs and lips allows the engagement members to be easily released with a simple hand tool

1      such a screwdriver blade so that the frame assembly can be disassembled for repair or replacement.

2

3      While the invention has been shown in one of its forms, it is not thus limited and is susceptible to  
4      various changes and modifications without departing from the spirit thereof.

5